

PAT-NO: JP363190942A

DOCUMENT-IDENTIFIER: JP 63190942 A

TITLE: VARIABLE-FRICTION COEFFICIENT BRAKE
SHOE

PUBN-DATE: August 8, 1988

INVENTOR-INFORMATION:

NAME

UEDA, YOSHIAKI

NISHIMURA, KOICHI

SASAKI, YOSHIMI

ASSIGNEE-INFORMATION:

NAME

KK UEDASA CHUZOSHO

COUNTRY

N/A

APPL-NO: JP62022500

APPL-DATE: February 4, 1987

INT-CL (IPC): F16D069/00

US-CL-CURRENT: 188/250B

ABSTRACT:

PURPOSE: To arbitrarily obtain many kinds of brake shoes different to an average coefficient by dividing a brake shoe into a plurality of brake shoe split pieces having a specified friction coefficient and selectively combining and arranging the split pieces to be detachably mounted on a brake shoe holder.

CONSTITUTION: A dovetail groove 2 is recessed on a brake shoe mounting surface of a brake shoe holder 1, and four brake shoe split

pieces 3a~3d
having a specified friction coefficient are respectively
formed integral with
back plates 4a~4d to be stuck thereto. The sliding
projection piece is
detachably fit in the dovetail groove 2, and stopper plates
5 projecting on
both end openings are fixed by bolts 6. Thus various brake
shoes 3 different
in an average friction coefficient can be obtained
arbitrarily by selectively
combining and arranging brake shoes respectively having a
specified friction
coefficient. Accordingly it is possible to easily and
quickly obtain an
average friction coefficient of a brake shoe according to
the running condition
and running environment of a vehicle.

COPYRIGHT: (C)1988,JPO&Japio

----- KWIC -----

Document Identifier - DID (1):
JP 63190942 A